





## RHO1

## Hold-down Hook





## Features & Benefits:

- Whip Retaining Hook for Fiberglass Whips
  - Non-powered, Threaded Mount Whip
  - Non-powered, Quick Disconnect Mount Whip
  - Powered, Threaded Mount Whip
  - Powered, Quick Disconnect Mount Whip

Weight	Overall Dimensions		
	Length	Width	Height
.09 LBS 0.04 (kg)	2.63" 66.80 (mm)	0.44" 11.18 (mm)	1.50" 38.10 (mm)



Other Various Mounting Options Available Upon Request! (Permanent, Temporary, Hitch, Specialty)

RH01:

## Available Whip Mounting Options: (Threaded/Quick Disconnect)

**Heavy Duty Spring Mounts** (Quick Disconnect, Threaded Whips)



c:519.309 Stainless Steel d:519·30B Zinc Plated Steel (Powered)

**Heavy Duty Spring Mounts** (Quick Disconnect, Threaded Whips)



c:519.309 Stainless Steel d:519:30B Zinc Plated Steel (Non-Powered)

Steel Thread Mounts



a:519.343.RCA b:519.343 (Powered)

Steel Quick Disconnect Mounts



b: SWQD-R: RCA Type power connector w/RCA type pigtail,

DS-SW-RH01-RevB

For More Information Call or Visit Us Online Today!

602.424.2500

F: 602.424.9777

E: Sales@DriverIndustrial.com

2677 192nd St. #107 Surrey, BC V3Z 3X1 CANADA

2115 W. Mountain View Rd.

Phoenix, AZ 85021 USA

**ADDRESS:** 

CAN

USA

604.560.5080

**F**; 604.560.5090

**E** Sales Canada @ Safety Whips.com