



## WC-U0650

General Purpose

PRIVER



Testing & qualification is required for individual vehicle for correct product selection to meet site requirements. Advised GVW is a guide only. This will vary due to environmental factors. Please complete an adequate risk assessment before using chocks. Do not use chocks if chocks are damaged.

## Part #: WC-UO650

Tire Size (up to)	46" (116.84cm)
Height	8.50" (21.59cm)
Width	9.00" (22.86cm)
Length	11.50" (29.21cm)
Weight	6 lbs (2.72kg)
Max. GVW	35 Ton

## HIGHLIGHTS:

- Light weight with tough urethane construction
- Maximum Gross Vehicle Operating Weight (GVW) = 35 Ton
- 3rd party tested for compliance
- (70,000lbs / 31,751.47kg)
- Complies with NFPA 1901 and NFPA 1906 Standards
- Resistant to oils, fuels and solvents
- Built-in carrying handle
- High visibility color used for safety
- Holes for rope, chains & mounting brackets
- Tire sizes up to 46in. Use a minimum of (2) UO650 chocks.



\*Multiple Colors Available Upon Request!

DS-TORO-WC-U0650-Re

## ADDRESS:

2115 W. Mountain View Rd. Phoenix, AZ 85021 USA

2677 192nd St. #107 Surrey, BC V3Z 3X1 CANADA USA

For More Information Call or Visit Us Online Today!

T: 602.424.2500

F: 602.424.9777

E: Sales@DriverIndustrial.com

CAN T: 604.560.5080

F: 604.560.5090

E: SalesCanada@SafetyWhips.com