



WC-UY750

Heavy Equipment

A Brand of

DRIVER
INDUSTRIAL


Driver Industrial Products - Color shown are indicative only and may vary due to printing.

Testing & qualification is required for individual vehicle for correct product selection to meet site requirements.

Advised GVW is a guide only. This will vary due to environmental factors. Please complete an adequate risk assessment before using chocks. Do not use chocks if chocks are damaged.

Part #: WC-UY750

Tire Size (up to)	105" (266.70cm)
Height	10.00" (25.40cm)
Width	15.00" (38.10cm)
Length	18.00" (45.72cm)
Weight	19 lbs (8.62kg)
Maximum Payload Capacity	165 Ton (149,685.48kg)
Max. GVW (Maximum Gross Vehicle Operating Weight)	550,000lbs (249,475.80kg)

HIGHLIGHTS:

- Tough urethane construction
- Rated for vehicles with a Maximum Gross Vehicle Operating Weight (GVW) of 550,000lbs (249,475.80kg)
- Maximum Payload Capacity = 165 Ton (149,685.48kg)
- 3rd party tested for compliance
- ANSI compliant color written guidelines on proper chocking procedures
- Complies with NFPA 1901 and NFPA 1906 Standards
- Resistant to oils, fuels and solvents
- Strong carrying handle on the backside of the chock
- High visibility color used for safety
- Holes for mounting brackets
- Tire sizes up to 105in. Use a minimum of (2) UY750 chocks.

DS-TORO-WC-UY750-RevD
Release Date: 10/2/21

ADDRESS:

2115 W. Mountain View Rd.
Phoenix, AZ 85021 USA

2677 192nd St. #107
Surrey, BC V3Z 3X1 CANADA

For More Information Call or Visit Us Online Today!

USA
T: 602.424.2500
F: 602.424.9777
E: Sales@DriverIndustrial.com
CAN
T: 604.560.5080
F: 604.560.5090
E: SalesCanada@SafetyWhips.com